

HOTONMC TENGZHOU HOTON MACHINERY.CO.,LTD

ADD:NO.1099 CHUNTENG EAST ROAD, SHANNAN STREET,
TENGZHOU CITY, ZAOZHUANG CITY, SHANDONG PROVINCE

Tel:+86-632-5633796 Email:info@hotonmachinery.com www.hotonmc.com

Radial Drilling Machine Z3032x10



SPECIFICATIONS	Z3032X10
Max. drilling dia(mm)	32
Spindle stroke(mm)	150
Column diameter	200
Spindle end taper	MT.4
Maximum allowable feed resistance of spindle (N)	5300
Spindle speed series	108,162, 262, 398, 665, 1000
Spindle feed amount of 3 n	0.10, 0.16, 0.25
Distance from spindle nose to base surface (maximum and minimum) (mm)	1060 to 220
Distance from spindle center to main column busbar (maximum and minimum) (mm)	910~200
Rocker rotary angle	360°
Swing arm lifting speed (m/min)	1.21
Lifting motor power (KW)	0.75
Main motor power (KW)	1.5/2.2
Dimension(L*W*H)	1400x660x2000
Net weight	1600 kg

Skype:hotonmachinery Phone/Wechat/WhatsApp:86-13506328892